


## Coro moon piano v cover pro datasheet

LED recessed spotlight with fireball light source (downlight non-tiltable) for hollow ceilings or solid ceilings with ceiling box. model with cover ring for magnetical attachment. The spotlight is mounted with a simple tension spring mechanism and requires no screw fittings. Version with remote power supply unit, connection to external constant current power source (driver). Dimmable via customer-supplied dimmable power supply unit. The innovative LED fireball technology creates a special lighting effect - direct, downward-facing light and atmospheric illumination by the fireballs indirect light. The fireball as a light source has a light cone of 30°.





### technical data Coro moon piano v cover pro

properties	material	aluminium, glass, PVD coated, painted, plastic
	weight	0.8 kg
surface	tube	matt white, matt black
	cover	gold, matt gold, rose gold polished, matt silver, phantom polished, black phantom polished, dark chrome polished
Occhio LED	average life time	>50.000 hrs
	energy efficiency class	This product contains a light source of energy efficiency class F (2200–3500 K, 2700 K, 3000 K) or E (2700–4000 K, 4000 K)
	power	LED 9W
	color rendering index	CRI Ra 92
	color temperature (color consistency)	single color: 2700 K, 3000 K, 4000 K (2-step) color tune: 2200–3500 K (2-step) 2700–4000 K (2-step)
electricity	dimming	with suitable power supply unit
	connection	single color (1-channel): max. $500\text{mA}/18\text{VDC}$ color tune (2-channel): max. $1000\text{mA}$ total current ( $I_1+I_2/9\text{VDC}$ per channel
	permitted operating conditions	ambient temperature 10-30°C, for indoor use only










### Occhi**o**

# Coro moon piano v cover pro lighting effects





#### moon

direct, glare-free light, beam angle approx. 30°

optics: Occhio fireball

power: high color 9 W

 $\begin{array}{ccc} \text{luminous flux:} & 2700\,\text{K} & 670\,\text{lm} \\ & 3000\,\text{K} & 720\,\text{lm} \end{array}$ 

 4000 K
 820 lm

 2200–3500 K
 510–660 lm

 2700–4000 K
 580–710 lm