



Coro piano v cover pro datasheet



LED recessed spotlight with fixed lens optics and 60° light cone (downlight non-tiltable) for hollow ceilings or solid ceilings with ceiling box. model with cover ring for magnetical attachment. The spotlight is mounted with a simple tension spring mechanism and requires no screw fittings. Version with remote power supply unit, connection to external constant current power source (driver). Dimmable via customer-supplied dimmable power supply unit.



technical data Coro piano v cover pro

properties	material	aluminium, glass, PVD coated, painted, plastic
	weight	0.7 kg
surface	tube	matt white, matt black
	cover	gold, matt gold, rose gold polished, matt silver, phantom polished, black phantom polished, dark chrome polished
Occhio LED	average life time	> 50.000 hrs
	energy efficiency class	This product contains a light source of energy efficiency class F (2200–3500 K, 2700 K, 3000 K) or E (2700–4000 K, 4000 K)
	power	LED 9W
	color rendering index	CRI Ra 92
	color temperature (color consistency)	single color: 2700K, 3000K, 4000K (2-step) color tune: 2200–3500K (2-step) 2700–4000K (2-step)
electricity	dimming	with suitable power supply unit
	connection	single color (1-channel): max. 500 mA / 18 VDC color tune (2-channel): max. 1000 mA total current (I ₁ + I ₂) / 9 VDC per channel
	permitted operating conditions	ambient temperature 10–30°C, for indoor use only

Coro piano v cover pro
lighting effects



lens
direct light, beam angle approx. 60°

optics:	lens	
power:	high color	9 W
luminous flux:	2700 K	430 lm
	3000 K	460 lm
	4000 K	520 lm
	2200–3500 K	310–410 lm
	2700–4000 K	360–430 lm